


ROUND SPRING OPEN/POWER CLOSE

SPRING OPEN /POWER CLOSE DAMPERS USE TWO WIRES TO POWER THE DAMPER CLOSED & IT AUTOMATICALLY SPRINGS OPEN WHEN POWER IS REMOVED. THE ZONE PANEL IS RESPONSIBLE FOR SUPPLYING A 24VAC SIGNAL TO EITHER THE PC (POWER CLOSED) TERMINAL OF THESE DAMPERS. ECOJAY'S SPRING DAMPERS PROVIDE A TOP QUALITY ROUND DAMPER AT A BUDGET-DRIVEN PRICE POINT.

- **RELIABLE & QUIET SPRING ACTUATOR**
- **HEAVY DUTY GALVANIZED DAMPER WITH 1 CRIMPED & 2 BEADED ENDS**
- **PRECISION CONSTRUCTION & QUALITY PARTS FOR LONG-LIFE & QUIET OPERATION**
- **360° FULL-DIAMETER POLY GASKET FOR LOWEST LEAKAGE SEAL**
- **ALL METAL SHAFT WITH NYLON BUSHINGS & TENSION CLIPS TO ENSURE FREE MOVEMENT**



DAMPERS


D	S	U	S	D
DAMPER	SUPPLY	ROUND	SPRING	DIAMETER

PART

DSUS06
DSUS07
DSUS08
DSUS09
DSUS10
DSUS12
DSUS14
DSUS16

D

6"
7"
8"
9"
10"
12"
14"
16"



SPECIFICATIONS

TUBE (CAN):	22 - 24 GA. GALVANIZED STEEL
BLADE:	URETHANE (RUBBERIZED) GASKET
SHAFT:	5/16" ROUND ALUMINUM
BUSHINGS:	HARDENED NYLON
WIRING:	18 OR 20 AWG (CLOSE - PC, COM -24VAC COMMON)
MOUNTING:	ANY ORIENTATION, FLEX DUCT, HARD DUCT, SPIRAL DUCT, STARTING COLLAR, ETC
ACTUATOR (DIRECT DRIVE)	MODEL # ASDM-2 MOTOR-CLOSE / SPRING-OPEN
	VOLTAGE: 24VAC
	POWER: 2.5VA / 60HZ, 10 VA
	TORQUE: 45 IN-OZ (MOTOR) 20 IN-OZ (SPRING)
	TRAVEL TIME: 30 SEC (CLOSE) 8 SEC (OPEN)
	TRAVEL ANGLE: 90 DEG (FULL OPEN/CLOSE)
SET SCREW	ALLEN/HEX: 3/16"



**ECOJAY
PRODUCTS
LIMITED
WARRANTY**